

ZHENGZHOU SUNRISE REFRACTORY CO., LTD

Sunrise REF13008-Fused Magnesia brick TY-DMZ-98

FUSED MAGNESIA BRICK

Specifications

Fused Magnesia Brick Refractory

- 2.CCS:60mpa,RUL:1700
- 3.Good erosion resistance
- 4. High quality
- 5.Reasonable price

Fused Magnesia Brick Features:

Excellent performance of basic slag resistance, high refractoriness, thermal stability, anti-erosion and anti-peeling

Excellent strength of pressure bending, abrasion proof

Excellent performance of high-temperature firing, high rates of associative property, anti-erosion ability

Excellent thermal shock resistance and spalling resistance

Excellent ability of high refractoriness, anti-erosion of alkaline residue;

High temperature load of refractoriness under load. High mechanical strength

High temperature resistance excellent corrosion resistance

Resistance to spalling

The products are fused magnesia as main raw material, after a reasonable size

distribution, high pressure forming, high-temperature sintering. The product has

WEB: WWW.SUNRISEREFRACTORY.COM



ZHENGZHOU SUNRISE REFRACTORY CO., LTD

strong resistance to slag corrosion ability and high temperature dimensional stability. Mainly used in glass furnace regenerator, the upper part.

Application:

it is mainly applied to the regenerators of glass kilns and other high temperature glass furnaces.

Physical and Chemical Index

Item		Behaviors
		Fused Magnesia Brick
		TY-DMZ-98
Chemical composition	MgO %	≥97.5
	SiO ₂ %	≤0.5
	CaO %	≤0.6
Apparent Porosity %		≤15
Cold Crushing Strength Mpa		≥60
0.2Mpa Refractoriness Under Load T _{0.6}		≥1700
Bulk Density g/cm ³		≥3.05
Thermal Stability 950°C Wind cycles		≥20

TEL: +86-371-63838939 FAX: +86-371-63835539 EMAIL: SUNRISE@SUNRISEREFR.COM

ADD: NO.36, FENGCHAN ROAD, ZHENGZHOU, HENAN, CHINA

WEB: WWW.SUNRISEREFRACTORY.COM